



Order no.: 116006

Rung mast hanging ladder

Number of rungs

- 6
- 8
- 10
- 12
- 14
- 16
- 20

Specification

Ladder length 1.85 m	Number of steps/rungs 6 rungs	Outer width 350 mm	Depth of side-rails 58 mm	Max. load capacity 200 kg
Weight 9 kg	Transport dimensions 2130 x 470 x 415 mm, 9 kg	Business division MUNK Günzburger Steigtechnik	Order no. 116006	Price € 671.00

Facts

- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Hanging hook, Ø 320 mm, made of galvanised steel and chains with snap hook for maximum stability
- Non-slip ladder shoes
- Rung distance: 280 mm
- Load hanging vertically: 200 kg (higher loads on request)

Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life
(including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Certificates



18KFP0134-02 -
Test Certificate
"Bauart geprüft"

Valid in



DIN EN 131-3:2007
PAK-
ANFORDERUNG
FÜR GS -
ABSCHNITT
3.1(PAH-
REQUIREMENT
FOR GS - CL. 3.1)
AFPS GS 2014:01
PAK
EK5/AK1 17-1:2017
DIN EN 131-1:2016
DIN EN 131-2:2017

Corporate certifications

on sustainability criteria



Management
System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108612548



Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022

