



Order no.: 044508

## Step shelf ladder, rotating for double shelf

Number of steps

- 6
- 7
- 8
- 9
- 10
- 11
- 12

### Specification

Working height 3.91 m	Step design Steps	Number of steps/rungs 8 steps	Step width 350 mm	Step depth 80 mm
Step/Rung distance 235 mm	Vertical hook-in height 3.06 m	Ladder length 2.28 m	Base area 1.16 m	Inclination 70 °
Outer width 400 mm	Castor diameter 80 mm	Max. load capacity 150 kg	Design type Mobile   Rotatable   With castors	Transport dimensions (plus packaging) 2323 x 580 x 86 mm, 7 kg
Transport dimensions (plus packaging) 2 1390 x 45 x 45 mm, 2.98 kg	Transport dimensions (plus packaging) 3 400 x 198 x 155 mm, 2.56 kg	Transport dimensions (plus packaging) 4 400 x 198 x 155 mm, 2.56 kg	Transport dimensions (plus packaging) 5 1047 x 405 x 105 mm, 3.5 kg	Business division MUNK Günzburger Steigtechnik
Order no. 044508				

### Facts

- Step shelf ladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm

- 4-fold edged step-to-side-rail connection
- For double shelves with aisle widths up to 1.60 m (variations up to 20 mm are compensated for by the chassis)
- Ladder easy to move thanks to smooth-running roll-top
- Self-locking spring-loaded castors, Ø 80 mm, at the lower end
- Non-slip ladder shoes
- Step spacing: 235 mm
- Ladder width: 400 mm (without castors)
- Ladder width with castors: 580 mm
- Ladder inclination: 70°
- Maximum load: 150 kg
- Note: Shelf ladders are manufactured in standard lengths stated here as well as individually made to measure. Please indicate the exact vertical hook-in height – the price includes the next higher ladder and a flat rate for changes of 51.00 euros RRP excluding VAT. Shelf ladders made to size are non-returnable

### Scope of supply

- Instructions for use and operation: 1 x
- Ladder: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size

- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---

### Added value

---

#### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



#### Versatile solutions

- Ladders available in standard lengths or individual dimensions
- Available with and without roll-top as well as a rotatable version
- Optional spring-loaded castors
- For single and double-sided shelves



#### Rail system

- Made-to-measure production of the rail system
- Easy assembly of all components



## Corporate certifications

---

### Standards for quality and sustainability



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548



**Nachhaltigkeit**  
**EcoVadis**  
sustainable supply management  
CSR-Rating in Silber 2022

