



Order no.: 063262

Wall anchor w. Clamping bracket, adjustable, 215-275 mm, galvanised steel

Wall clearance min [mm]

165

215

275 375

Specification

Wall anchor	Wall distance min.	Wall distance max.	Adjustment range	Material
Single	215 mm	275 mm	60 mm	Galvanised steel
Transport dimensions 260 x 60 x 115 mm, 1.28 kg	Business division MUNK Günzburger Steigtechnik	Order no. 063262		

Facts

- Adjustment range enables flexible use
- Robust construction for secure hold
- A firm hold even during intensive use
- Adjustable wall anchor

Scope of supply

■ Wall anchor: 1 x

Information on sustainability criteria



Corporate certification: ISO 9001

■ Corporate certification: ISO 14001

■ Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures







Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





Corporate certifications

Standards for quality and sustainability









