



Order no.: 063502

Safety doors without fall protection rail

Specification

Entry/Exit Safety door Material Aluminium Transport dimensions 605 x 585 x 90 mm, 4 kg

Business division MUNK Günzburger Steigtechnik Order no. 063502

Facts

- Compliant with DIN EN ISO 14122-4
- Automatically closing
- Material: Bright aluminium
- Simple to assemble
- Adjustable passage dimension approx. 520– 560 mm
- Door can be hinged left or right

Scope of supply

Security door: 1 x

Installation material: 1 x

Assembly instructions: 1 x



Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

RoHS

■ REACH

■ The MUNK Group complies with a Code of Conduct

The Supply Chain Act does not apply due to our size

The materials used are listed in the technical specification

Resource-saving production: own photovoltaic systems

Energy-efficient consumption during production: LED lighting

Repairability, durability and quality: 15-year warranty on series products made in Germany

Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.

Socially acceptable working conditions in production: fair wages, gender equality

 Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic

No health hazards for the users

More product pictures





Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





Corporate certifications

Standards for quality and sustainability









