



Order no.: 011218

Roof hook for plain tiles, brown

Model versions

Anthracite grey powder-coated

Brown powder-coated

Red powder-coated

Red-brown powder-coated

Galvanised steel

Specification

Colour version Braun pulverbeschichtet	Transport dimensions (plus packaging) 425 x 210 x 30 mm, 1.12 kg	Business division MUNK Günzburger Steigtechnik	Order no. 011218
--	---	--	---------------------

Facts

- Delivery includes with grooved nails
- Coloured hooks are hot-dip galvanised and powder-coated
- To be mounted centrally on the rafters
- At least two hooks are needed for the first ladder and at least one hook is needed for each additional ladder
- Complies with Construction Products Ordinance (BauPVO) 305/2011 (EU) and DIN EN 517
- Safety roof hooks in accordance with DIN EN 517 must be installed on roofs with an inclination of 22.5° to 75°. They must be distributed over the roof surface as follows:
 - Upper row < 1.0 m below the ridge
 - Intermediate rows in each case < 5.0 m distance from the row above

- Lower row < 1.5 m above the eaves, in each case measured in the roof pitch
- The horizontal distance between the safety hooks of a row must not exceed 2.0 m. To be used for eaves heights above 3.0 m

Scope of supply

- Roof hooks: 1 x

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life
(including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Corporate certifications

Standards for quality and sustainability

