



Order no.: 052705

Folding platform ladder with narrow undercarriage



Number of steps

5	6	7	8	10	12	14

Specification

Working height	Step design	Number of steps/rungs	Platform included as step	Platform height
3.15 m	Steps	5 steps	Yes	1.15 m
Platform length	Platform width	Step depth	Step/Rung distance	Height
650 mm	600 mm	80 mm	235 mm	2.19 m
Total length folded 2.75 m	Base spread	Inclination	Outer width	Stabiliser width
	1.4 m	70 °	650 mm	850 mm
Depth of side-rails 73 mm	Depth of side-rails, support 58 mm	Max. load capacity 150 kg	Design type Single-sided access Freestanding With chassis beam	Ballast weight 30 kg
Weight incl. ballast weight 67 kg	Transport dimensions 2780 x 760 x 220 mm, 29 kg	Transport dimensions 2 860 x 220 x 262 mm, 37.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 052705

Facts

- Platform ladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm



- Spacious platform with grooves for secure footing (650 x 600 mm)
- 4-fold edged step-to-side-rail connection
- With handrail on both sides, 3-sided, 1,000 mm high railing with knee and foot rails as well as safety rope
- Support part with narrow undercarriage and ballast weight for high stability
- Folds for compact storage thanks to sturdy steel hinges (when ballast weight is on the outside)
- Particularly suitable for narrow shelving aisles etc.
- Integrated Ø 125 mm fixed castors with locking device for quick transportation when folded out
- nivello® ladder shoes with patented 2-axis inclination technology
- Generous sized tool tray
- Outer width: 650 mm (without stabiliser)

Step spacing: 235 mmLadder inclination: 70°

Maximum load: 150 kg

Scope of supply

Ladder: 1 x

Instructions for use and operation: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct



- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures







Added value

Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



The movable ladder shoe sets new standards in stability

Learn more



Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Castors

- Ergonomic and comfortable handling
- Simple movement from place to place



Certificates





Corporate certifications



Standards for quality and sustainability









