MUNK
Sicherheit. Made in Germany.



Order no.: 033208

Double-sided rung ladder wood

Number of rungs

2x4 | 2x5 | 2x6 | 2x7 | 2x8 | 2x10

Specification

Working height 2.5 m	Step design Rungs	Number of steps/rungs 2x 4 rungs	Step/Rung distance 280 mm	Height 1.14 m
Ladder length 1.23 m	Base spread 830 mm	Lower outer width 500 mm	Upper outer width 380 mm	Depth of side-rails 60 mm
Max. load capacity 150 kg	Design type Freestanding | Double-sided access	Transport dimensions (plus packaging) 1225 x 490 x 123 mm, 6.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 033208

Facts

- Double-sided rung ladder made of wood
- Side-rails made of finger-jointed pine or knot-free Caroline pine, rungs made of ash
- Pegged rung-to-side-rail connection, resulting in smooth side-rail surface
- Sturdy steel hinges
- Supplied as standard with practical bucket hook
- Spreader lock with two galvanized steel chains
- Rung distance: 280 mm

- Maximum load: 150 kg
- These products are covered by the statutory warranty

Scope of supply

- Ladder: 1 x

More product pictures







Added value

Industrial grade

- Sturdy processing for demanding applications (e.g. 4-fold edging)
- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories

Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on TRBS 2121 Part 2 has been summarised on our Service page
- Read our tips and tricks on how to calculate working height



Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022