

Order no.: 062021

Wall anchor, adjustable,
stainless steel

Wall clearance min [mm]

150	165	200	280	360
-----	-----	-----	-----	-----



Specification

Suitable for Schachtleitern	Wall distance min. 165 mm	Wall distance max. 215 mm	Adjustment range 50 mm	Transport dimensions (plus packaging) 200 x 122 x 50 mm, 0.92 kg
Business division MUNK Günzburger Steigtechnik	Order no. 062021	Material Edelstahl V4A		

Facts

- Adjustable wall anchor
- For shaft ladders
- Stainless steel
- Note: 4 wall brackets are required for ladders with 4 - 9 rungs, 6 wall brackets for ladders with 10 - 15 rungs and 10 wall brackets for ladders with 16 - 24 rungs
- Note: Wall plugs and bolts are to be used to fasten the ladder to the shaft rather than nuts and screwed bolts when their suitability has been verified at the place where the ladder is used. They have to be selected in accordance with the force acting on the ladder anchoring point as stated by the manufacturer.

- Dowels and screws for attachment to the wall are not included in the delivery. Please contact well-known dowel suppliers for information.

Scope of supply

- Wall anchor: 1 x
- Assembly instructions: 1 x

More product pictures



Corporate certifications

Standards for quality and sustainability

