



Order no.: 070500

Mobile de-icing frame

Model versions

Specification

| | | | | |
|---------------------------|--|--|----------------------|-----------------------|
| Platform height 2.8 m | Railing height 1 m | Height 3.9 m | Step width 600 mm | Total width 1.32 m |
| Scaffolding length 3 m | Transport dimensions 3122 x 1325 x 3904 mm, 196 kg | Business division MUNK Günzburger Steigtechnik | Order no. 070500 | |

Facts

- For the safe and quick removal of ice and snow loads from trucks and commercial vehicles. Also ideal for repairs to truck tarpaulins and superstructures.
- Compact, stable aluminium scaffolding system
- Easy to move on four swivel castors and can therefore also be used in any location
- Maintenance-free, durable and weather-resistant
- Inclined ascent with handrail and 100 mm deep steps made of perforated aluminium cover (R13) plus lower step

- Non-slip platform made of aluminium grating (R13) with trapdoor. The hole pattern also prevents water pooling and the retention of dirt and snow
- 4-sided railings with foot and knee boards for a high level of safety at work
- Simple assembly without the need for tools thanks to push-fit connections and automatically closing locking claws
- Design takes into account DIN EN 1004
- Maximum load: 1.5 kN/m²
- Fast delivery (3–5 working days)
- Production in compliance with European standards DIN EN ISO 14122 and DIN EN 1004
- This product is made to order and cannot be returned

Scope of supply

- Installation material: 1 x
- Assembly instructions: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany

- **Recyclability:** Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- **Socially acceptable working conditions in production:** fair wages, gender equality
- **Economical and recyclable packaging:** no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- **No health hazards for the users**

More product pictures



Added value

Product configurator

Configuring, enquiring about and ordering individual products could not be easier with our [product configurator](#) for stairs, bridging steps and mobile platform stairs. Simply enter your required dimensions and versions step by step, and a rotating 3D model will appear in real time. To save your configuration and request a quotation requires a login which will be set up for you by our Sales team.



Safety railing

- Railings and handrails on both sides ensure a high level of safety at work
- Fixed size or telescopic safety door



Modular kit system

- Individually and cost-efficiently combinable for the respective requirement
- Platform heights from 1.25 to 3.0 m
- Three different platform lengths can be selected

Ascent

- Non-slip designs for secure footing
- All kinds of different materials can be selected with non-slip classes from R 9 to R 13 – suitable for the specific application purpose



Modular walkway systems

- For a wide range of indoor applications in production, warehouses, as access to machines, as a walkway along building walls or as practical access for de-icing commercial vehicles in the winter months
- Thanks to innovative modular construction, walkway systems can be assembled conveniently, cost-effectively and yet precisely to meet individual requirements
- The platform height of the walkway systems can be individually determined between 1.25 and 3.0 metres. The desired total length is achieved by way of combining three different walkway lengths
- The modules can be easily assembled using pre-assembled modules, securely connected to one another and fastened to the underlying surface using foot brackets
- The maintenance-free modules are manufactured as a stable, corrosion-resistant aluminium construction with a supporting frame.
- Maximum load: 1.5 kN / m², step load 150 kg, total load 300 kg
- Access to the walkway conveniently via stairs 45° with handrails on both sides and automatically closing safety door.
- The delivery from the factory is made in pre-assembled modules for quick and simple assembly in accordance with the enclosed assembly instructions

Note

When assembling a walkway, only modules with the same platform height can be combined. Please contact us if you need different platform heights on a walkway system. This also applies if you need walkway systems for outdoor use, as they are primarily designed for indoor use (with the exception of de-icing systems).

Corporate certifications

Standards for quality and sustainability



Management
System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108612548



Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022

