MUNK
Sicherheit. Made in Germany.



Order no.: 070500

Mobile de-icing frame

Model versions

Specification

Platform height 2.8 m	Railing height 1 m	Height 3.9 m	Step width 600 mm	Total width 1.32 m
Scaffolding length 3 m	Transport dimensions (plus packaging) 3122 x 1325 x 3904 mm, 196 kg	Business division MUNK Günzburger Steigtechnik	Order no. 070500	

Facts

- For the safe and quick removal of ice and snow loads from trucks and commercial vehicles. Also ideal for repairs to truck tarpaulins and superstructures.
- Compact, stable aluminium scaffolding system
- Easy to move on four swivel castors and can therefore also be used in any location
- Maintenance-free, durable and weather-resistant
- Inclined ascent with handrail and 100 mm deep steps made of perforated aluminium cover (R13) plus lower step

We reserve the right to make technical changes and price changes.

- Non-slip platform made of aluminium grating (R13) with trapdoor. The hole pattern also prevents water pooling and the retention of dirt and snow
- 4-sided railings with foot and knee boards for a high level of safety at work
- Simple assembly without the need for tools thanks to push-fit connections and automatically closing locking claws
- Design takes into account DIN EN 1004
- Maximum load: 1.5 kN/m²
- Fast delivery (3–5 working days)
- Production in compliance with European standards DIN EN ISO 14122 and DIN EN 1004
- This product is made to order and cannot be returned

Scope of supply

- Installation material: 1 x
- Assembly instructions: 1 x

More product pictures







Added value


Product configurator

Configuring, enquiring about and ordering individual products could not be easier with our product configurator for stairs, bridging steps and mobile platform stairs. Simply enter your required dimensions and versions step by step, and a rotating 3D model will appear in real time. To save your configuration and request a quotation requires a login which will be set up for you by our Sales team.



Safety railing

- Railings and handrails on both sides ensure a high level of safety at work
- Fixed size or telescopic safety door



Modular kit system

- Individually and cost-efficiently combinable for the respective requirement
- Platform heights from 1.25 to 3.0 m
- Three different platform lengths can be selected

Ascent

- Non-slip designs for secure footing
- All kinds of different materials can be selected with non-slip classes from R 9 to R 13 – suitable for the specific application purpose



Modular walkway systems

- For a wide range of indoor applications in production, warehouses, as access to machines, as a walkway along building walls or as practical access for de-icing commercial vehicles in the winter months
- Thanks to innovative modular construction, walkway systems can be assembled conveniently, cost-effectively and yet precisely to meet individual requirements
- The platform height of the walkway systems can be individually determined between 1.25 and 3.0 metres. The desired total length is achieved by way of combining three different walkway lengths
- The modules can be easily assembled using pre-assembled modules, securely connected to one another and fastened to the underlying surface using foot brackets
- The maintenance-free modules are manufactured as a stable, corrosion-resistant aluminium construction with a supporting frame.
- Maximum load: 1.5 kN / m², step load 150 kg, total load 300 kg
- Access to the walkway conveniently via stairs 45° with handrails on both sides and automatically closing safety door.
- The delivery from the factory is made in pre-assembled modules for quick and simple assembly in accordance with the enclosed assembly instructions

Note

When assembling a walkway, only modules with the same platform height can be combined. Please contact us if you need different platform heights on a walkway system. This also applies if you need walkway systems for outdoor use, as they are primarily designed for indoor use (with the exception of de-icing systems).

Corporate certifications

Standards for quality and sustainability

