



Order no.: 041645

## Double-sided stepladder with clip-step R13



Number of steps

|      |     |     |     |     |     |     |      |
|------|-----|-----|-----|-----|-----|-----|------|
| 2x3  | 2x4 | 2x5 | 2x6 | 2x7 | 2x8 | 2x9 | 2x10 |
| 2x12 |     |     |     |     |     |     |      |
| 2x14 |     |     |     |     |     |     |      |

### Specification

|                                                      |                              |                                      |                                                      |                                                                              |
|------------------------------------------------------|------------------------------|--------------------------------------|------------------------------------------------------|------------------------------------------------------------------------------|
| Working height<br>4.3 m                              | Step design<br>Steps         | Number of steps/rungs<br>2x 12 steps | Step depth<br>80 mm                                  | Step/Rung distance<br>235 mm                                                 |
| Type of non-slip<br>protection<br>clip-step R13      | Height<br>2.79 m             | Base spread<br>2.22 m                | Inclination<br>70 °                                  | Lower outer width<br>700 mm                                                  |
| Depth of side-rails<br>73 mm                         | Width of side-rails<br>25 mm | Max. load capacity<br>150 kg         | Design type<br>Freestanding  <br>Double-sided access | Transport dimensions<br>(plus packaging)<br>2990 x 692 x 213<br>mm, 21.83 kg |
| Business division<br>MUNK Günzburger<br>Steigtechnik | Order no.<br>041645          |                                      |                                                      |                                                                              |

### Facts

- Stepladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- 4-fold edged step-to-side-rail connection
- clip-step R13 step padding for certified non-slip protection on all accessible steps

- Conical side-rail guide for safe stance
- nivello® ladder shoes with patented 2-axis inclination technology
- ergo-pad® grip area with clamping mechanism
- Sturdy, solid aluminium ladder joint, securely screwed in place
- Spreader lock with two high-strength polyester straps
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

### Scope of supply

- Ladder: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality

- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

---

## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



The movable ladder shoe sets new standards in stability


[Learn more](#)



### clip-step R 13 step padding

Certified non-slip protection for step ladders

- Fulfills the requirements of the highest possible non-slip class R 13 thanks to aluminium oxide particles
- Improves work safety in wet and oil-contaminated environments
- Applied up to the maximum accessible step as a visual check
- Retrofittable, available as a spare part and also in yellow in selected lengths (RAL 1021)



### ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



#### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



#### Certificates



25KFP0049-01 -  
Test Certificate  
"Bauart geprüft"

Valid in

DIN EN 131-1:2019  
DIN EN 131-2:2017  
DIN EN 131-3:2018  
EK5/AK1 17-  
02.4:2021  
PAK-  
ANFORDERUNG  
FÜR GS (PAH  
REQUIREMENT  
FOR GS) AFPS GS  
2019:01 PAK

Corporate certifications

Standards for quality and sustainability

