



Order no.: 071338

Hinged loading bridge LB 400

Type

LB 300

LB 400

LB 500

Specification

Length 3.6 m	Total length max. 3.92 m	Extendable No	Foldable Yes	Total width 1.05 m
Clear width 1 m	Bridgeable distance 3.4 m	Material Aluminium	Permissible total load 300	Surface Aluminium corrugated
Toe board height 63 mm	Mobile No	Wheelchair accessible Yes	Business division MUNK Rettungstechnik	Order no. 071338

Facts

- Loading bridge made of non-slip grooved aluminium
- Can be folded in the middle for space-saving transport
- For safe loading and unloading of vehicles and trailers
- With side toe boards
- For professional use

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

Standards for quality and sustainability



Management System
ISO 9001:2015
ISO 14001:2015

www.tuv.com
ID 9108612548



Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022

