



Order no.: 068250

Wall anchor, adjustable, 165-205 mm, stainless steel

Wall clearance min [mm]

165 215 275

## Specification

Wall anchor	Wall distance min.	Wall distance max.	Adjustment range	Material
Single	165 mm	205 mm	40 mm	Stainless steel
Transport dimensions 200 x 135 x 60 mm, 1.18 kg	Business division MUNK Günzburger Steigtechnik	Order no. 068250		

#### **Facts**

- Flexible adjustment range from 215 to 275 mm
- Ideal for vertical ladders
- Adjustable wall anchor

## Scope of supply

■ Wall anchor: 1 x

## Information on sustainability criteria



Corporate certification: ISO 9001

■ Corporate certification: ISO 14001


■ Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

### More product pictures







#### Added value

#### Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





# Corporate certifications

### Standards for quality and sustainability









