MUNK
Sicherheit. Made in Germany.



Order no.: 043803

Double-sided stepladder 250 kg with clip-step R13

Number of steps

2x3 | 2x4 | 2x5 | 2x6 | 2x7 | 2x8

Specification

Working height 2.2 m	Step design Steps	Number of steps/rungs 2x 3 steps	Platform included as step Yes	Step depth 80 mm
Step/Rung distance 235 mm	Type of non-slip protection clip-step R13	Height 670 mm	Inclination 70 °	Lower outer width 440 mm
Depth of side-rails 73 mm	Width of side-rails 25 mm	Max. load capacity 250 kg	Design type Freestanding | Double-sided access	Transport dimensions (plus packaging) 740 x 433 x 200 mm, 5 kg
Business division MUNK Günzburger Steigtechnik	Order no. 043803			

Facts

- Stepladder made of aluminium
- Stable rectangular tube side-rails
- clip-step R13 step padding for certified non-slip protection on all accessible steps
- Grooved steps with a depth of 80 mm R10
- 4-fold edged step-to-side-rail connection

- Conical side-rail guide for safe stance
- nivello® ladder shoes with patented 2-axis inclination technology
- ergo-pad® grip area with clamping mechanism
- Sturdy, solid aluminium ladder joint, securely screwed in place
- Spreader lock with two high-strength polyester straps
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 250 kg
- Please note: Wear and tear of the corundum grit caused by use is typical of this material. Individual particles may also become dislodged during use.

Scope of supply

- Ladder: 1 x

More product pictures








Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



The movable ladder shoe sets new standards in stability


Learn more



clip-step R 13 step padding

Certified non-slip protection for step ladders

- Fulfils the requirements of the highest possible non-slip class R 13 thanks to aluminium oxide particles
- Improves work safety in wet and oil-contaminated environments
- Applied up to the maximum accessible step as a visual check
- Retrofittable, available as a spare part and also in yellow in selected lengths (RAL 1021)




ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on TRBS 2121 Part 2 has been summarised on our Service page
- Read our tips and tricks on how to calculate working height



Certificates

25KFP0215-01 - Test Certificate "Bauart geprüft"

Valid in

DIN EN 131-1:2019
DIN EN 131-2:2017
DIN EN 131-3:2018
EK5/AK1 19-01:2019
PAK-ANFORDERUNG FÜR GS (PAH REQUIREMENT FOR GS) AFPS GS 2019:01 PAK

MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022