



Order no.: 068506

Safety door with fall protection rail

Material

Stainless steel

Galvanised steel

Specification

Entry/Exit Safety door	Material Stainless steel	Weight 22 kg	Transport dimensions 1300 x 710 x 125 mm, 22 kg	Business division MUNK Günzburger Steigtechnik
Order no. 068506	Price € 1,720.00			

Facts

- Automatically closes thanks to concealed spring mechanism
- With pre-assembled fall protection rail, incl. upper and lower detachable end protection
- For mounting on steel / stainless steel vertical ladders only
- Exit side-rail as mandatory accessory



Scope of supply

Security door: 1 x

Installation material: 1 x

Assembly instructions: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



All fixed ladders / vertical ladders at a glance:

- Single-flight vertical ladders in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders on buildings
- DIN 14094-1: Multiple-flight <u>emergency ladder</u> <u>systems (emergency ladders)</u>
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders on machinery



Corporate certifications

on sustainability criteria









