

Order no.: 030409

ML bridging platform, foldable





Working height [mm]

2500

2700

Specification

Working height 2.7 m	Platform height 700 mm	Platform length 1.74 m	Platform width 290 mm	Step/Platform surface Aluminium tibial plate
Non-slip class R10	Base area length 2.33 m	Base area width 700 mm	Design type Double-sided access Foldable	Number of steps/rungs 2x 3 rungs
Platform included as step No	Depth of side-rails 58 mm	Max. load capacity 150 kg	Material Aluminium	Transport dimensions 1740 x 700 x 112 mm, 10.5 kg
Business division MUNK Günzburger Steigtechnik	Order no. 030409			

Facts

- Lightweight, sturdy aluminium design
- Quick and easy installation thanks to folding feet
- Grooved rungs for safe ascent and descent
- Safe working on platform made of aluminium chequered plate
- Non-slip plastic shoes



Rung spacing 280 mm

Maximum load: 150 kg

Scope of supply

Working plank: 1 x

Instructions for use and operation: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users



More product pictures








Added value

Flexibility

- Easy to transport, space-saving in storage
- Sufficient space; depending on version for up to two persons plus working implements and material



Non-slip plastic shoes

- Ensure secure stance
- High impact and abrasion resistance
- Simple replacement in the event of wear



Corporate certifications

Standards for quality and sustainability









