

Order no.: 051095

## ML platform ladder



Number of steps

4

5

6

7

8

## Specification

Working height 3.1 m	Step design Stufen	Number of steps/rungs 5 steps	Platform included as step Ja	Platform height 1.11 m
Platform height up to railing 1 m	Step depth 80 mm	Step/Rung distance 235 mm	Height 2.17 m	Total length folded 2.31 m
Base spread 1.15 m	Inclination 70 °	Lower outer width 620 mm	Depth of side-rails 73 mm	Depth of side-rails, support 58 mm
Max. load capacity 150 kg	Design type Freistehend   Einseitig begehbar	Transport dimensions (plus packaging) 2310 x 630 x 279 mm, 11.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 051095

## Facts

- Platform ladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- Height of the partial enclosure 1,000 mm
- Large, trapeze-shaped platform (400 / 360 x 425 mm)

- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance
- Two pre-assembled handrails for safe ascent and descent
- 'safe-cap' ladder joint
- Non-slip ladder shoes
- Spreader lock with two high-strength polyester straps
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

### Scope of supply

- Ladder: 1 x
- Handrail (mounted): 2 x
- Assembly instructions: 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.

- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

### More product pictures



## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### Ladder joint safe-cap

- Smooth ladder joint with large contact surface and sturdy plastic protective cap
- The 6 rivets and thicker wall thickness provide for greater stability and protection at this sensitive point on the ladder, increasing its service life
- The safe-cap protects the ladder when in use, when loading and storing, as well as the contact surfaces, walls, truck loading areas and the joint itself




### Sponsored by BG BAU

Specification subject to conditions; for the latest information please visit the BG BAU website (statutory accident insurance company for the construction and construction related services in Germany). Since 2014, the BG BAU has been promoting the purchase of platform ladders, step stools and ladder accessories with single-sided and double-sided access. All members of the BG BAU profit from this. This aims to prevent work accidents on building sites and improve ergonomic working practices. For more information by BG BAU, please visit:

[www.bgbau.de/service/angebote/arbeitsschutzpraemien](http://www.bgbau.de/service/angebote/arbeitsschutzpraemien)

A brief overview of the subsidy and an overview of our eligible products can be found on our website under [know-how](#).

## Certificates



25KFP0480-01 -  
Type-tested

Valid in

DIN EN 131-1:2019  
DIN EN 131-2:2017  
DIN EN 131-3:2018  
EK5/AK1 17-  
02.4:2021  
PAK-  
ANFORDERUNG  
FÜR GS (PAH  
REQUIREMENT  
FOR GS) AFPS GS  
2019:01 PAK

## Corporate certifications

---

### Standards for quality and sustainability

