

Order no.: 051097

ML platform ladder



Number of steps

- 4
- 5
- 6
- 7
- 8

Specification

Working height 3.6 m	Step design Steps	Number of steps/rungs 7 steps	Platform included as step Yes	Platform height 1.58 m
Platform height up to railing 1 m	Step depth 80 mm	Step/Rung distance 235 mm	Height 2.64 m	Total length folded 2.81 m
Base spread 1.46 m	Inclination 70 °	Lower outer width 680 mm	Depth of side-rails 73 mm	Depth of side-rails, support 58 mm
Max. load capacity 150 kg	Design type Freestanding Single-sided access	Transport dimensions (plus packaging) 2806 x 685 x 279 mm, 14.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 051097

Facts

- Platform ladder made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- Height of the partial enclosure 1,000 mm
- Large, trapeze-shaped platform (400 / 360 x 425 mm)

- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance
- Two pre-assembled handrails for safe ascent and descent
- 'safe-cap' ladder joint
- Non-slip ladder shoes
- Spreader lock with two high-strength polyester straps
- Step spacing: 235 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x
- Handrail (mounted): 2 x
- Assembly instructions: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.

- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories




Ladder joint safe-cap

- Smooth ladder joint with large contact surface and sturdy plastic protective cap
- The 6 rivets and thicker wall thickness provide for greater stability and protection at this sensitive point on the ladder, increasing its service life
- The safe-cap protects the ladder when in use, when loading and storing, as well as the contact surfaces, walls, truck loading areas and the joint itself



Certificates



25KFP0480-01 -
Type-tested

Valid in

DIN EN 131-1:2019
DIN EN 131-2:2017
DIN EN 131-3:2018
EK5/AK1 17-
02.4:2021
PAK-
ANFORDERUNG
FÜR GS (PAH
REQUIREMENT
FOR GS) AFPS GS
2019:01 PAK

Corporate certifications

Standards for quality and sustainability

