



Order no.: 020818

2-section rung push-up  
extension ladder with  
standard stabiliser



Number of rungs

|      |      |      |      |      |      |      |
|------|------|------|------|------|------|------|
| 2x8  | 2x9  | 2x10 | 2x11 | 2x12 | 2x13 | 2x14 |
| 2x15 | 2x16 |      |      |      |      |      |
| 2x17 | 2x18 |      |      |      |      |      |

Specification

|                              |                              |                                             |                                                                             |                                                      |
|------------------------------|------------------------------|---------------------------------------------|-----------------------------------------------------------------------------|------------------------------------------------------|
| Working height<br>10.3 m     | Step design<br>Rungs         | Number of steps/rungs<br>2x 18 rungs        | Step/Rung height<br>30 mm                                                   | Step depth<br>30 mm                                  |
| Step/Rung distance<br>280 mm | Retracted length<br>5.3 m    | Extended length<br>9.18 m                   | Outer width<br>420 mm                                                       | Stabiliser width<br>1.2 m                            |
| Depth of side-rails<br>98 mm | Width of side-rails<br>25 mm | Design type<br>To lean against   2-<br>part | Transport dimensions<br>(plus packaging)<br>5292 x 425 x 173<br>mm, 30.2 kg | Business division<br>MUNK Günzburger<br>Steigtechnik |
| Order no.<br>020818          |                              |                                             |                                                                             |                                                      |

Facts

- Rung push-up extension ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection

- Simple height adjustment from rung to rung thanks to insertion hook with automatically engaging lift-off protection
- Upper ladder from size 14 rungs with wall wheels
- Corrosion-resistant guide fixtures
- Upper ladders up to 3.0 m with nivello® ladder shoes
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Standard stabiliser with non-slip ladder shoes with optimum width for the selected product. Ensures maximum stability and safe ascent for straight ladders over 3.0 m. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m

### Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x
- Stabiliser (enclosed separately): 1 x

### Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct

- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

---

## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



### Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



### Standard stabiliser

Safe, standards-compliant ascent for straight ladders over 3.0 m

- Different stabiliser widths, suitable for the selected ladder length
- Non-slip ladder shoes
- Individually available as spare part



#### roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



#### Certificates



25KFP0347-01 -  
Test Certificate  
"Bauart geprüft"

Valid in

DIN EN 131-1:2019  
DIN EN 131-2:2017  
DIN EN 131-3:2018  
EK5/AK1 17-  
1.3:2021  
PAK-  
ANFORDERUNG  
FÜR GS (PAH  
REQUIREMENT  
FOR GS) AFPS GS  
2019:01 PAK

Corporate certifications

Standards for quality and sustainability

