



Order no.: 063975

Exit step for SI door with
fall protection rail,
galvanised steel

Clearance [mm]

- 100
- 150
- 200
- 250
- 300

Specification

Material Galvanised steel	Clearance 300 mm	Transport dimensions (plus packaging) 625 x 395 x 115 mm, 5.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 063975
------------------------------	---------------------	---	--	---------------------

Facts

- For widening the uppermost rung and reducing the gap width at the exit
- Dimensions approx. 620 x 100 – 300 mm
- Consisting of grooved rungs, incl. 2 clamp connectors for ladder side rails

Scope of supply

- Step stool: 1 x
- Installation material: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001

- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

Added value

Optimum planning

- Practical planning aids (available as [Downloads](#)) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



Corporate certifications

Standards for quality and sustainability

