

Order no.: 027919

Push-fit frame 135/56

Number of rungs





Specification

Length 680 mm	Height 560 mm	Scaffolding width 1.35 m	Transport dimensions 680 x 1340 x 60 mm, 3 kg	Business division MUNK Günzburger Steigtechnik
Order no. 027919	Suitable for Mobile scaffolding			

Facts

- Easy to install thanks to sophisticated push-fit system
- Lightweight for easy handling and transport
- For scaffolding width of 1.35 m

Scope of supply

Push-fit frame: 1 x

Information on sustainability criteria



- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Corporate certifications

on sustainability criteria



