



Order no.: 070550

# Access guarding Enclosure

# Specification

Transport dimensions 788 x 792 x 2200 mm, 40.6 kg Business division MUNK Günzburger Steigtechnik Order no. 070550

#### **Facts**

- Access guard for fixed ladders with lockable swing door and fixed side parts
- Lightweight and sturdy aluminium construction
- Can always be opened from the inside using a lever
- Can be opened from the outside using a fire brigade three-bolt lock in accordance with DIN 14925 (key not included)
- Delivery time: approx. 20 working days

### Scope of supply

Enclosure with panic lock: 1 x



### Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

RoHS

■ REACH

■ The MUNK Group complies with a Code of Conduct

The Supply Chain Act does not apply due to our size

The materials used are listed in the technical specification

Resource-saving production: own photovoltaic systems

Energy-efficient consumption during production: LED lighting

Repairability, durability and quality: 15-year warranty on series products made in Germany

Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.

Socially acceptable working conditions in production: fair wages, gender equality

 Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic

No health hazards for the users

## More product pictures





#### Added value

#### Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





# Corporate certifications

### Standards for quality and sustainability









